

SOUND SPECIFICATIONS PURPLE STAGE (MARCH 2017)

Capacity: 400 standing

Stage: 8 x 6m / 26 x 20ft (plus wings 2m on both sides), clearance 6m

Power 3 x 3 phase 32A, 4 x 16A CEE form

PA SYSTEM

Speakers and amps	4 Adamson SX18 top 4 Adamson A215 sub 1 Lab Gruppen PLM10000 amp 1 Lab Gruppen PLM20000 amp Lake Controller
FOH console	1 Soundcraft MH-3 40ch analogue desk
Analogue siderack	1 KT DN-370 equalizer 1 TC Electronics M3000 multi-effect 1 Yamaha SPX-990 multi-effect 1 Lexicon LXP-15 II 1 TC Electronics D-Two multi-effect 4 Drawmer DS201 dual gate 2 Drawmer DL241 dual compressor 2 dbx 166 dual compressor

MONITORSYSTEM

Wedges and subs	9 L'Acoustics 115XT inc. PFL wedge 1 L'Acoustics SB15 sub 5 L'Acoustics LA8 4 channel amp
Monitor Console	1 Soundcraft Vi1 console 1 Soundcraft/Studer stagebox 48 in / 8 out
Microphones / DI's	8 Shure SM58 6 Shure SM57 2 Shure Beta 58 2 Shure Beta 57 2 Shure Beta 52 2 Shure Beta 91

Microphones / DI's	<ul style="list-style-type: none"> 1 Beyer Dynamic M88 5 Sennheiser e604 2 Sennheiser e609 3 Sennheiser MD421 MKII 2 AKG C214 2 Shure SM81 2 Oktava MK-012 (paired) 2 Radial J48 active DI 5 BSS AR-133 active DI 2 SCV DIP MKIII passive DI 2 Monarch DIB 100 passive DI
Stands	<ul style="list-style-type: none"> 10 K&M tall stands 10 K&M small stands 1 K&M straight stand / round base
Installed infra	<ul style="list-style-type: none"> 4 CAT5 network cable 1 glassfibre multimode cable 2 Coax w/ BNC connector 1 LK150 + breakouts 48ch 1 LK37 for additional channels
Additional	ASL BS216 + 2 beltpack / Beyer DT109 headphones / ASL beacon

Max. average sound level: 103dB(A), will be measured and logged according to the national covenant.